

EMC.DES-4122.v2022-07-02.q20

□□□□:	DES-4122
□□□□:	Specialist - Implementation Engineer, PowerEdge Exam
□□□:	EMC
□□ □□ □□□:	20
□□:	v2022-07-02
# □□ □:	405
# □□ □□□:	200
https://www.krdump.com/EMC.DES-4122.v2022-07-02.q20.html	

NEW QUESTION: 1

Dell EMC PowerEdge R740 □□□□ vFlash SD □□□ □□□ □□□□□. □□ □□□ □□ vFlash □□ □ □□ □□□ □□□ □ □□□□.

□□ □□□□ □□□□□?

- A. □□ □□□ □□□□ BOSS□ □□ vFlash□ □□
- B. 13G □□ 14G □□□ □□ vFlash SD □□ □□□
- C. □□ □□□ □□□□ NVMe □□□□□ □□ vFlash□ □□
- D. 14G □□□ □□ vFlash SD □□ □□□

Answer: D ([LEAVE A REPLY](#))

NEW QUESTION: 2

BIOS/UEFI □□ □□□□ □□ □□□ □□□ □□□ □□□ □□□□□?



Answer:

System Information

Power State	ON
Model	PowerEdge R640
Host Name	
Operating System	
Operating System Version	
Service Tag	PSTC123
BIOS Version	2.54
iDRAC Firmware Version	4.10.10.10
IP Address(es)	123.123.123.123
iDRAC MAC Address	84:7b:12:34:56:78
License	Enterprise

Recent Logs

Severity	Description	Date and Time
✓	The input power for power supply 2 has been restored.	Mon 23 Mar 2020 12:06:20
✓	The power supplies are redundant.	Mon 23 Mar 2020 12:06:12
✗	The power input for power supply 2 is lost.	Mon 23 Mar 2020 12:06:09
✓	The power supplies are redundant.	Fri 14 Feb 2020 12:38:08
✓	Power supply 1 is operating normally.	Fri 07 Feb 2020 08:59:30

□□: □ □□□ □□ □□□ □□□□ □□ □□□□□ □□ □□(x)□□ □□□.

- Fan 3A RPM is less than the lower critical threshold. Successfully logged in using PTAdmin, from 123.123.123.7 and WS-MAN. Manual log collection completed.
- Power supply redundancy is lost. No login activity. Manual log collection failed.
- Under voltage fault detected on power supply 2. Previous log entry was repeated 12 times. System log collection completed.
- Under voltage fault detection on power supply 1. Successfully logged in using vxpsvc, from 123.123.123.8 and GUL. No log collection has been created.

- A. □□ B
- B. □□ A
- C. □□ C
- D. □□ D

Answer: C ([LEAVE A REPLY](#))

NEW QUESTION: 6

Dell EMC PowerEdge 2000 2x 120GB RAID controller BOSS controller.

- A. RAID 5
- B. RAID 10
- C. RAID 1
- D. RAID 0

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 7

Dell EMC PowerEdge 14G RDIMM DIMM controller.

- A. NVDIMM RDIMM controller.
- B. RDIMM NVDIMM controller.
- C. NVDIMM RDIMM controller.
- D. LRDIMM RDIMM controller.

Answer: A ([LEAVE A REPLY](#))

NEW QUESTION: 8

14G Dell EMC Poweredge controller SupportAssist controller.



Answer:

□ □□□□□ □□□ □□ □□□ □□□□□□.

NEW QUESTION: 9

Dell EMC PowerEdge □□□□ □□□ RACADM□□□ □□ □□□ □□□ □□□□□?

- A. OpenManage □□□□□□ RACADM□ □□□
- B. SSH □□ Telnet□ □□□□ iDRAC□ □□□
- C. Dell Toolkit□ □□□□ RACADM□ □□□
- D. Boot Manager□ □□ iDRAC□ □□□

Answer: B ([LEAVE A REPLY](#))

NEW QUESTION: 10

Dell EMC PowerEdge R740xd □□□□ □□□ □ □□ □□ □□□ □□□□ □□□ □□□□ □□□

- A. 6x2 5" □□□□
- B. 2x3.5" □□□□
- C. 3.5□□ □□□□ 4□
- D. 8x2 5□□ □□□□

Answer: B ([LEAVE A REPLY](#))

NEW QUESTION: 11

iSM □□ □□□ □□ □□□ □□□□□ □□□ □□□□□?

- A. OS □□ □□□ □□□□□
- B. □□ □□□□ □□□□ □□□□□.
- C. □□ □□□□ □□□
- D. OS □□ □□□ □□□□

Answer: ([SHOW ANSWER](#))

NEW QUESTION: 12

1DRAC8□ 1DRAC9□ □□ □□□□ □□□□□?

- A. iDRAC8 □□ □□ □□□ □□□ □□□ □□□□□.
- B. iDRAC9 □□ □□ □□□ □□/□□ □□□ □□
- C. iDRAC9□ HTML5 □□ GUI□ □□□□□.
- D. iDRAC8□ HTML5 □□ GUI□ □□□□□.

Answer: D ([LEAVE A REPLY](#))

NEW QUESTION: 13

□□□□ iDRAC9 □□□ □□ □□□ □□□□□□□□ □□□ □ □□□□□?

- A. iDRAC □ GUI□ □□□ □□□ □□ □□ □□□ □□□□ □□ □□ □ LCC□ □□ □□□□ □□□□□□□.

- 1 PowerEdge R640 Server
- 1 Hot-plug Power Supply, 750W - qty 1
- Jumper Cord - C13/C14, 4M, 250V, 10A - qty 1
- Broadcom 57412 Dual Port 10GbE SFP+ and 5720 Dual Port 1GbE BASE-T rNDC - qty 1
- SFP+ SR Optic, 10GbE - qty 2
- Dell Networking, Cable, SFP+ to SFP+, 10GbE, Copper Twinax DAC, 3 Meter - qty 2
- CAT6 Patch cable 5 Meters - qty 2

Which of the following is NOT included in the configuration for a Dell PowerEdge R640 server?

- A. 750W Hot-plug Power Supply - qty 1
- B. Dell Networking, Cable, 40GbE(QSFP+) - 4 x 10GbE SFP+ Copper Twinax DAC, 3 Meter - qty 2
- C. C20 ~ C21, PDU Jumper Cord, 250V, 16Amp, 3.5m - qty 2
- D. 1100W Hot-plug Power Supply - qty 1

Answer: C (LEAVE A REPLY)

DES-4122 dumps are available on DumpTop. Visit <https://www.dumptop.com/EMC/DES-4122-dump.html> for more information. **30%OFF Special Discount: KrDump**

NEW QUESTION: 17

A Dell PowerEdge R640 server is configured with iDRAC(RAID 1), 2x 4TB NL-SAS drives, Lifecycle Controller OS, and 2048GB of memory. Which of the following is NOT a valid configuration for the server?

- A. 4TB drives, 2048GB memory (2TB) configuration.
- B. Lifecycle Controller OS, 2048GB memory configuration.
- C. Lifecycle Controller OS, 2048GB memory, 2TB(2) configuration.
- D. F2 BIOS, UEFI boot mode configuration.

Answer: B (LEAVE A REPLY)

NEW QUESTION: 18

Which of the following is NOT a valid configuration for a Dell PowerEdge R640 server?

- A. 32GB memory, 64GB cache configuration.
- B. 32GB memory, 64GB cache, 2TB(2) configuration.
- C. 32GB memory, 64GB cache, 2TB(2) configuration.
- D. UAC configuration.

Answer: A (LEAVE A REPLY)

□□□ □□□□□. <https://www.dumptop.com/EMC/DES-4122-dump.html> (62 Q&As Dumps,
30%OFF Special Discount: **KrDump**)